

AD 69 45 96

DIGITAL COMPUTER NEWSLETTER

The purpose of this newsletter is to provide a medium for the interchange, among interested persons, of information concerning recent developments in various digital computer projects



OFFICE OF NAVAL RESEARCH • MATHEMATICAL SCIENCES DIVISION

Vol. 2, No. 1

1 January 1960

TABLE OF CONTENTS

1. Institute for Advanced Study Computer
2. Whirlwind I
3. Raytheon SDC Computer
4. CALDIC, University of California, Berkeley
5. Institute for Numerical Analysis Computer
6. NBS Interim Computer
7. The Bell Computer - Model VI
8. Data Conversion Equipment
9. The EDSAC, Cambridge University, England
10. Computer, Manchester University, England
11. Digital Computers, Birkbeck College, University of London
12. Digital Computers in Sweden
13. Computer at Mathematisch Centrum, Amsterdam

Handwritten note: Add ...
D D C
RECEIVED
OCT 16 1959

Institute for Advanced Study Computer

Since the last Newsletter most of the work at the Institute for Advanced Study has been devoted to bringing the Arithmetic Organ into its final form and to producing the full scale Williams-type memory organ.

At this time quite extensive tests have been made of the multiplier operating at high duty cycle on several periodic tests. These tests have been quite successful; and there have been no difficulties nor malfunctions of the unit.

The full 40-fold Williams-type memory is being fabricated now, and it is hoped that in the near future it will be ready for its initial engineering tests, at which time the results will be reported.

Whirlwind I

The Whirlwind I arithmetic element, central control, and 32-register test storage have been operating together for several months. No extended reliability runs have been made, but a number of different test and display programs have been run without error for hours at a time. The test programs were designed to use as many parts of the computer as possible. The display programs include the solution of a second order differential equation with means for manual adjustment of the constants. The solutions are computed point by point and displayed on an oscilloscope by means of a binary-to analog decoder. Some 200 points are calculated per sweep of the scope, and this is repeated 15 times per second.

The 5-digit multiplier has been in continuous operation multiplying 31 x 31 and checking each answer at a repetition rate of 15,000 per second. From July 15 to December 30 there have been 5 breakdowns due to known causes and a total of 14 single random unexplained errors.

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield, Va. 22151

This document has been approved
for publication and sale; its
distribution is unlimited.

4

One Eastman reader-recorder unit has been received and is undergoing tests with the computer input-output registers and control.

Eight electrostatic storage tubes have been accepted as satisfactory for Whirlwind I; an additional 8 are believed to be satisfactory. The initial bank of 16 tubes, storing 256 binary digits each, will be completed and installed during January and February.

Raytheon SDC Computer

The basic designs for almost all components of the Raytheon computer have been completed. The machine's one-thousand word internal memory will occupy a volume equivalent to one standard radio relay rack. Final design of the external memory units is nearing completion. The tape handling mechanism and recording circuits are operating satisfactorily.

During the past few months, techniques for printing permanent marks on the back of magnetic recording tape have been perfected. The marks are used to catalogue each of the three-thousand blocks of data in the external memory units. Photoelectrically operated hunt controls permit rapid access to any of the one-hundred thousand external memory positions.

CALDIC, University of California, Berkeley

At the present time, the logical design has been completed, the techniques to be used in the magnetic-drum memory have been developed, and some circuits have been developed, including the shifting registers. The drawings for the magnetic-drum and heads are being prepared and construction will begin soon. Construction of some electronic components will also begin soon, while investigation of other circuit techniques is being carried on. Input and output are in the design stage. The present estimate of the tube count is 2000, and floor space required is estimated to be 100 square feet.

Institute for Numerical Analysis Computer

There are two types of chassis in the arithmetic unit consisting of 40 chassis each. Construction of one type has been completed and these chassis are now being put through resistance and DC voltage checks. Prototypes of the other type have been approved and a contractor is proceeding with production. The required driver chassis to supply signals to the arithmetic unit have also been constructed. The chassis of the control unit have been completed and checked out, and work is proceeding on the final details of the interconnecting wiring of the chassis.

A production model of the cathode ray tube memory unit has been built, tested, and found to be entirely satisfactory. A contract for the signal amplifier that goes in this unit has been awarded to a local contractor who is proceeding with production. Requests for quotations for fabricating 45 cathode ray tube memory units have been asked from contractors at the present time.

The heater transformers of the power supply are now being constructed by a local transformer company and will be delivered within a week. The DC power supply specifications have been prepared and various bids have been obtained from local contractors for fabricating these units.

NBS Interim Computer

Essentially the complete control system for the computer has been assembled and successfully operated. In addition to verifying the design procedures this assembly provides a series of signals useful in the testing of arithmetic and input-output components as they are completed. The design of the arithmetic unit is complete, and its physical fabrication nearly finished. Also the input-output equipment suitable for the initial use of punched paper tape is nearly as far along.

The machine is now laid out so that in addition to the original 512 words of acoustic memory, to be delivered in February, it is possible to use simultaneously an electrostatic memory of any size

up to a total machine capacity of 4048 words. This electrostatic memory would operate in parallel in spite of the serial nature of the machine's arithmetic unit, and would decrease the machine's average computation time by a factor of the order of 2 or 3. Circuitry for such a memory is now being assembled and if successful it is planned to construct a complete memory of 512 or 1024 words.

Provision has been made in the machine design for the possible future addition of commands for accumulation, high-speed shut, and operation with a so-called base number, which under certain circumstances is automatically added to the addresses of a command, and commands having addresses which refer to relative rather than absolute memory locations--this being convenient in the multiple use of subroutines.

The Bell Computer - Model VI

The Bell Computer - Model VI is a general purpose digital relay computer with an electronically or tape controlled program. The electronic program arrangement has access to combinations of several semi-permanent built-in standard formulae. The solution of any standard problem requires that the problem tape simply furnish the formula number and the input data of the problem. Non-standard problems are programmed by individually coded instructions on the problem tape.

Data Conversion Equipment

The Telecomputing Corporation, Burbank, California, reports the development of a "Telereader" to facilitate the rapid transfer of data from film, oscillograms or graphs to numeric form in punched cards. Another device, the "Teleorder" converts a magnitude as represented by an electrical voltage or current, a mechanical rotation or linear travel, a hydraulic pressure or a displacement on a photographic record, to a discreet number of pulses or counts, which are accumulated by an electronic counter. The numbers standing in the counter can be read-out and punched into IBM cards for reduction or subsequent handling.

In general, auxiliary equipment, designed by the company, is required to couple the physical systems being measured to the recorders. Conversion of the binary numbers punched on the cards to decimal numbers can be accomplished on an IBM calculator associated with the equipment.

Also reported is work on an automatic high-speed plotting machine which will be actuated by IBM punch cards and will record up to 50 points per minute on a Cartesian coordinate system. The location of the desired points will be accomplished by actually counting grid lines on the graph paper.

THE EDSAC, CAMBRIDGE UNIVERSITY, ENGLAND

This computer, containing about 3000 vacuum tubes, was completed by Dr. M. V. Wilkes and his co-workers at the University Mathematical Laboratory in June 1949. The 512 word memory consists of two batteries of 18 mercury acoustic delay lines, each line capable of storing 16 words of 35 binary digits including the algebraic sign. Each 35 binary digit word can be split into two smaller words. Since the pulse repetition rate is 500 k.c.p.s. access to the internal storage varies from about .2 to 1.2 milliseconds. Addition time is 1.5 milliseconds and multiplication 7.0 milliseconds. Since its completion, the EDSAC has been used for a number of simple computational problems, such as the calculation of prime numbers, tabulation of the complex gamma function, computation of the number "e" to 200 decimal places, and calculation of the Airy integrals. These problems have been carried out not so much for their intrinsic interest, but rather in order to gain experience with programming of problems for the EDSAC.

COMPUTER, MANCHESTER UNIVERSITY, ENGLAND

This computer was built by Professor F. C. Williams in the Electrical Engineering Laboratories and has operated successfully on test problems. It has an electrostatic storage of 128 words of 40 binary digits each and a magnetic storage of 1024 words. Each of the two storage tubes in the electronic memory has a capacity of 2,560 binary digits, and words are stored or read by scanning the desired

