



PHOTOGRAPHIC INTERPRETATION REPORT

# NEW SURFACE-TO-AIR MISSILE, MOSCOW PARADE 7 NOVEMBER 1963




CIA



DIA

Declass Review by  
NIMA/DOD

NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER





WARNING

This document contains information affecting the national defense of the United States, within the meaning of Title 18, sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law.

## NEW SURFACE-TO-AIR MISSILE, MOSCOW PARADE

7 NOVEMBER 1963

25X1C

[redacted]  
7 November 1963 revealed four surface-to-air missiles reported by the Soviets to be anti-missile missiles. The numerical designations 1240738, 1245211, and 1245215 are visible on three of the missiles; the designation of the fourth missile was not observed. The missiles are two-stage surface-to-air missiles on spe-

cially designed trailers towed by what are probably tractor versions of the MAZ 502 cargo truck (Figures 1 and 2). Each missile consists of a booster and a combination sustainer and warhead stage, with an overall length of [redacted] feet from the tip of the pressure probe to the rear of the booster nozzle. The overall length of the tractor-trailer is [redacted] feet.

25X1




FIGURE 1. MISSILE ON TRAILER.

25X1

25X



SECRET

NPIC/R-1585/63





FIGURE 2. MISSILE AND TRACTOR-TRAILER.

[Redacted]

25X

25X1D



bilizer fins. The booster stabilizer fins are opposed on axes of 45 degrees to the sustainer control and stabilizer fins. The booster is divided into a nozzle section [redacted] feet long and ranging from [redacted] feet in diameter, and a motor case [redacted] in diameter that mates with the sustainer nozzle skirt. Positioned on opposite sides of the missile forward of the booster stabilizer fins are two plugs, possibly cable connections. Located on the top and to the rear of the booster are two probable handling/hold-down couplings. No details on the booster nozzle can be furnished because of the cover plug.

25X1  
25X1  
25X1

The sustainer and warhead stage (Figures 4 and 5) measures [redacted] in length from the tip of the pressure probe to the edge of the sustainer nozzle skirt. The sustainer, excluding the warhead section (dark-toned area), is [redacted] long with a diameter of [redacted]. The diameter of the sustainer at the nozzle skirt is [redacted]. Positioned at the rear of the sustainer are four control fins, each with a surface area of [redacted].

25X1  
25X1  
25X1  
25X1  
25X1

25X1D The booster stage (Figure 3) has an overall length of [redacted] feet and a diameter of [redacted] feet.  
25X1D The diameter of the booster, including the length of each stabilizer fin, is [redacted] feet. The four stabilizer fins are positioned on axes of 90 degrees at the rear of the booster, and each has a surface area of [redacted] square feet. No control or trim tabs were observed on the booster sta-

SECRET




FIGURE 3. BOOSTER STAGE.

25X

square feet, which pivot on control-fin shafts protruding from the sustainer. The diameter of the sustainer, including the length of the control fins, is [ ] feet. Located forward of the control fins are four stabilizer fins positioned on axes of 90 degrees, each with a surface area of [ ] square feet. On at least one, and probably two, of the stabilizer fins are trim tabs with a control surface of [ ] square feet. Another unidentified appendage is observed forward of the trim tab. The overall diameter of the sustainer, including the length of the stabilizer fin, is [ ] feet. Located at the tip of each visible stabilizer fin is an antenna [ ] feet in length. It should be noted that the stabilizer antenna was missing on one of the missiles. In addition, two probable stabilizers [ ] feet in length are positioned on

an axis of 180 degrees at the front of the sustainer aft of the warhead section. External cableways of various lengths are visible on both sides of the sustainer. One external cableway connects the booster and sustainer stages. The warhead section of the missile (dark-toned area) measures [ ] feet in length. The curvature of the ogive cannot be determined accurately from available photography. The pressure probe measures [ ] feet in length, with a maximum diameter of [ ] and a minimum of [ ]

The tractor-trailer used for the missile has an overall length of [ ] feet; the missile trailer measures [ ] feet in length and [ ] feet wide. The dimensions of the unloaded trailer are probably different, as evidenced by the fold-down catwalks protecting the sustainer

25X1D

25X1D

25X1D

25X1D

25X1D

25X1D

25X1

25X1

25X1

25X1

25X1

25X1

25X1D



NPIC/R-1585/63




FIGURE 4. SUSTAINER AND PORTIONS OF BOOSTER AND WARHEAD.

25X




FIGURE 5. WARHEAD AND PORTION OF SUSTAINER.

25X

25X1D

Table 1. Dimensional Data on Missile and Tractor-Trailer

Overall length of missile (including pressure probe)	
Overall length of tractor-trailer	
<u>Booster</u>	
Length	
Diameter	
Diameter (including length of stabilizer fins)	
Surface area of each stabilizer fin	
<u>Sustainer</u>	
Length (including nozzle skirt)	
Length of nozzle skirt	
Diameter	
Diameter at junction of sustainer and nozzle skirt	
Diameter (including length of control fins)	
Surface area of each control fin	
Diameter (including length of stabilizer fins)	
Surface area of each stabilizer fin	
<u>Warhead</u>	
Length	
Concavity of ogive	
Length of pressure probe	
Maximum diameter of pressure probe	
Minimum diameter of pressure probe	
<u>Tractor-Trailer</u>	
Type (probable tractor version MAZ 500)	
Overall length	
Maximum width	




FIGURE 6. DIMENSIONAL DRAWINGS OF MISSILE AND TRACTOR-TRAILER.

SECRET

NPIC/R-1585/63

stabilizer fins. In such instances, the trailer dimensions would probably decrease in width. The trailer does not have a launch or erector capability and its design (one vertical booster stabilizer fin extends through the trailer carriage into a boot) necessitates a lifting device for removal of the missile from the trailer. The missile is supported by four and a suspect fifth cradle, at least one of which appears to be hand-cranked to the level of the missile. The missile is secured to the trailer by three tie-

down bands. One band, which is probably tightened by means of a wheel handcrank attached to the cradle support, is located on the forward end of the booster stage; the second is on the aft portion of the sustainer; and the third is on the forward section of the sustainer [ ] feet aft of the warhead. The third tie-down band has raised channels that permit passage of the external cableways.

25X1

At least seven frames are used to provide support for protective canvas covering.

#### REFERENCES

PHOTOGRAPHY

25X1C

[ ] 7 Nov 63. That in Figure 2 is classified CONFIDENTIAL and that in Figures 1, 3, 4, and 5 is classified SECRET.

REQUIREMENT

PC 895-63

NPIC PROJECT

J-409/63

SECRET



Approved For Release 2003/05/15 : CIA-RDP78B04560A001900010069-3

~~SECRET~~

Approved For Release 2003/05/15 : CIA-RDP78B04560A001900010069-3

~~SECRET~~



**NATIONAL  
SECURITY  
ARCHIVE**

This document is from the holdings of:

The National Security Archive

Suite 701, Gelman Library, The George Washington University

2130 H Street, NW, Washington, D.C., 20037

Phone: 202/994-7000, Fax: 202/994-7005, [nsarchiv@gwu.edu](mailto:nsarchiv@gwu.edu)